



PINNING M12 cable



C1: M12 Male C2: M12 Female

DESCRIPTION

- Spiralised dual air hose with implemented sensor / actuator cable
- Connector C1: M12, 5 pole, male
- Connector C2: M12, 5 pole, female
- Dual air hose: PUR, Blue/black, rd 8 x 1 mm
- Y-boots placed for cable protection, Raychem 382A023 or equivalent

| | | | | | | | | | | | | | | |
|---|--------------------------------------|--|---------------------------------------|------------|---|----------------------------------|--------|----------------------|----------|-----------|------------|------------|----------------------|------|
| Roughness acc. to ISO 1302 | Dimensions tolerated acc. to ISO 129 | Tolerances of form and position acc. to ISO 1011 | Dimensions in mm | C | Diam and Hose lenght changed | | | | 0508 | HS | 28-12-2020 | | | |
| | | | | D | Hose on both sides lengthensd | | | | 0508 | HS | 20-07-2021 | | | |
| <div>SIMCO IONTM</div> <div>An ITW Company</div> <div>WWW.SIMCO-ION.NL TEL: +31 (0)573 288333</div> | | | <div>XX</div> <div>Control dim.</div> | Rev. | | Description | | | | ECN | Chk. | Date | | |
| | | | | Range [mm] | 0,5-3 | >3-6 | >6-30 | >30-120 | >120-315 | >315-1000 | >1000-2000 | >2000-4000 | | |
| | | | | | | Copyright © SIMCO (Nederland) BV | Middle | ±0,1 | ±0,1 | ±0,2 | ±0,3 | ±0,5 | ±0,8 | ±1,2 |
| Name: Air hose 4m with device cord spiralised Cleanflex Easy | | | | | | | | | | | | Drawn: FW | Part no.: 6508004840 | |
| CAD GENERATED NOT AUTOMATICALLY UPDATED | | Date: 28-12-2020 | M: 1:20 | A3 |  | Check: HS | | Dwg. no.: 05084840/D | | 1/1 | | | | |